


# RS 8.2 CONCRETE



## RS 8.2 DESCRIPTION

Spray or roller applied novolac epoxy vinyl ester, flake filled basecoat with double 1.5-oz. chopped strand mat embed and double resin rich veil embed.



## COMMON AREAS OF USE

- Elevated temperature immersion service for strong acids and chemicals requiring pure resin rich finish coats
- Complies with NBS-15-69 corrosion barrier lining
- Steel or concrete tanks, vessels and reservoirs
- Repair or refurbishment of FRP corrosion barriers

## RS 8.2 DETAILS

<b>Surface Preparation</b>	SSPC-SP13 / NACE 6 - ICRI CSP 5 or greater	--	--
<b>Concrete Rehabilitation</b>	Series <a href="#">217</a> MortarCrete, Series <a href="#">215</a> Surfacing Epoxy or Primer + Series <a href="#">211-9111</a> Bulking Powder	As required.	As required.
<b>Prime Coat (Stripe)</b>	Series <a href="#">1407</a> Vinester*	4-6 mils DFT	275 sq ft / gal
<b>Mortar Coat</b>	Series <a href="#">1436</a> Vinester	20 mils DFT	65 sq ft/ gal
<b>Mat</b>	Series <a href="#">211-227</a> 1.5-oz Chopped Strand Mat	--	--
<b>Saturant Coat</b>	Series <a href="#">1416-900</a> Vinester	20 mils DFT	60 sq ft / gal
<b>Mat</b>	Series <a href="#">211-227</a> 1.5-oz Chopped Strand Mat	--	--
<b>Saturant Coat</b>	Series <a href="#">1416-900</a> Vinester	20 mils DFT	60 sq ft / gal
<b>Saturant Coat</b>	Series <a href="#">1416-900</a> Vinester + Series 1400 Color Pack	25 mils DFT	60 sq ft / gal
<b>Veil**</b>	451-A0010 or M524-ECR30S	--	--
<b>Saturant Coat</b>	Series <a href="#">1416-900</a> Vinester + Series 1400 Color Pack	25 mils DFT	60 sq ft / gal
<b>Veil**</b>	451-A0010 or M524-ECR30S	--	--

**120 mils DFT**

\*Do not use Series 1407 in wet or dry services of >180°F (82°C) or 200°F (93°C) spikes. Preference is direct-to-metal.

\*\*Contact your local Tnemec representative for specified veil.

**Note:** Coverage rates are theoretical (no loss). Reference Tnemec data sheets, application guides and construction details for more information.

Published technical data, instructions and pricing are subject to change without notice. Contact your Tnemec technical representative for current technical data, instructions and pricing. Warranty information: The service life of Tnemec's coatings will vary. For warranty, limitation of seller's liability and product information, please refer to Tnemec Product Data Sheets at [tnemec.com](http://tnemec.com) or contact your Tnemec technical representative. © Tnemec Company, Inc. RS82C